INTERNATIONAL ONE METRE CLASS

2022

CERTIFICATION CONTROL FORM - HULL AND APPENDAGES - CHECK LIST

H	Iull Re	egistration N	Tumber Certification Control Date	
C	wner		Official Measurer	
NB - MEASURERS This form is for your guidance in the certification process. It is not required to be sent to the Certification Authority , but may be retained by the Owner or the Official Measurer .				
	1. Certification control shall be carried out in accordance with the current Equipment Rules of Sailing except where varied bythe			
2.	ass rul The hais form	ull and apper	ndages shall comply with all the class rules in Sections D, E, F, G and H even if the rules are not mentioned on	
		•	if the equipment complies with the statement. Complete the Certification Control Form only if all items are with class rules Sections D, E, F, G and H. Consult your Certification Authority if there is any doubt.	
HU	HULL			
	1.	D.1.4	The registration number is marked in an easily visible location on a non-removable part of the hull , excluding fittings and corrector weights , by any of: painting, engraving, bonding, moulding.	
	2.	D.1.5	There is a deck limit mark , of 5 mm minimum diameter, displayed on the centre plane of the hull near the mast position.	
	3.	D.2.1	The hull construction materials do not include any of the following: (1) except for elastomeric material, expanded, foamed or honeycombed material and (2) fibre reinforcement material with a higher modulus of elasticity than glass fibre.	
	4.	D.2.2(a)	The hull is a monohull .	
	5.	D.2.2(b)	Except for trunking for the keel and rudder , the hull has no - a. voids in the water plane and/or underwater profile b. hollows in the plan view and/or underwater profile that exceed 3 mm c. transverse hollows in the under surface of the hull that exceed 3 mm when tested parallel to the water plane as in figure I.2.	
	6.	D.2.2(c)	The forward 10 mm, or more, of the hull is of elastomeric material.	
	7.	D.2.2(d)	The rudder is attached to the hull aft of the keel .	
	8.	D.2.3(a)	Fittings which contribute to the stiffness and/or strength and/or watertight integrity of the hull do not include materials prohibited by D.2.1. See #3 above.	
	10.	D.2.3(b)	Ball and/or roller bearings are used only in sheet control line blocks, mainsail boom sheet blocks and headsail boom sheet blocks .	
	11.	D.2.3(c)	All fittings are inboard of the hull shell or deck.	
		D.2.4	The remote control equipment consists only of some, or all, of the following: one or more receivers, one rudder control unit, one sheet control unit, battery pack(s), electric cables, connectors, switches, one device to indicate voltage or built in voltage indicator, voltage control device.	
API	PENDA	AGES		
Ш	13.	E.1.1	The keel complies with class rule E.1.1.	
	14.	E.3.2(a)	The keel and rudder are removable from the hull .	
	15.	E.3.2(b)(1)	The keel and rudder are not connected.	
	16.	E.3.2(b)(2)	The keel and/or rudder are not articulated.	
	17.	E.3.2(b)(2)	The keel and/or rudder have no openings through which water could flow when in use .	
	18.	E.4.1	The largest transverse dimension of the keel is 20 mm, or less, measured at any point 60 mm or more above the lowest point of the keel .	